

HT18 - 6 Ton



Standard Features

2" x 8" Treated Pine Deck	12,000 lb. Heavy Duty Landing Gear
(2) 6K Dexter Axles w/E-Z Lube Bearings	16" 10-ply Radial Tires
Tool Tray in Tongue	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	16,900 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	4,900 lbs.	Brakes	Electric / 12" x 2"
Maximum Payload	12,000 lbs. w/adequate hitch load	Wheels	16" x 6" Single 8-bolt
Overall Length	27'	Tires	LT235/85R16" 10-ply
Deck Length	21' (16' flat)	Jack Capacity	12,000 lbs.
Beavertail	5' cleated	Main Frame	10" Channel @ 15.3#
Ramps	5' cleated w/spring assist	Crossmembers	Double 3" Channel @ 7#
Overall Width	96"	Side Rails	6" Channel @ 8.2#
Deck Width	96"	Decking	2" X 8" Treated Pine
Deck Height	35"	Tie Downs	Rub Rail w/Stake Pockets
Hitch	2 1/2" Forged Eye	Lights	DOT Sealed Rubber-Mounted
Hitch Height	22" to 32"	Colors	Yellow or Black
Axles	2-6K Dexter		

Options

8WGN - Gooseneck w/adjustable 2 5/16" ball hitch	FAR - Fully Adjustable Ramps
LTBL - Lockable Toolbox Lid	8WADL - Additional Deck Length (4' Maximum)
8WOD - 2" x 8" Treated Oak Deck	8W102 - 102" Wide
SUR - Standup Ramps	MW - Modular Wiring
8WARL - Additional Ramp Length (1' Maximum)	STSLG - Single 2 Speed Landing Gear
FR - Feathered Ramps	TC - Trickle Charger for Break-A-Way
WIR&B - Wood Insert Ramps & Beavertail	7KA - 7K Dexter Axles w/16" 14-ply tires
3"EH - 3" Eye Hitch	STM - Spare Tire Mount
2 5/16"HDB - 2 5/16" Heavy Duty Ball Hitch	CO - Color Options: Red, Blue or Green
PSP - Paver Special: 6' Beavertail w/wood - 6' fully adjustable standup ramps w/wood and feathered end	