

HS14 - 6 Ton



Standard Features

2" x 8" Treated Oak Deck	12,000 lb. Heavy Duty Landing Gear
(2) 6K Dexter Axles w/E-Z Lube Bearings	16" 10-ply Radial Tires
Tool Tray in Tongue	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	16,100 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	4,100 lbs.	Brakes	Electric / 12" x 2"
Maximum Payload	12,000 lbs. w/adequate hitch load	Wheels	16" x 6" Single 8-bolt
Overall Length	22'	Tires	LT235/85R16" 10-ply
Deck Length	16' (14' flat)	Jack Capacity	12,000 lbs.
Beavertail	2' w/wood	Main Frame	10 Channel @ 15.3#
Ramps	5' cleated w/spring assist	Crossmembers	4" Channel @ 5.4#
Overall Width	96"	Side Rails	6" Channel @ 8.2#
Deck Width	96"	Decking	2" X 8" Treated Oak
Deck Height	28"	Tie Downs	4-1" D-rings
Hitch	2 1/2" Forged Eye	Lights	DOT Sealed Rubber-Mounted
Hitch Height	21" to 31"	Colors	Yellow or Black
Axles	2-6K Dexter		

Options

BWGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	BWADL - Additional Deck Length (4' Maximum)
LTBL - Lockable Toolbox Lid	BW102 - 102" Wide
ADR - Additional D-rings	MW - Modular Wiring
BWARL - Additional Ramp Length (1' Maximum)	STSLG - Single 2 Speed Landing Gear
FR - Feathered Ramps	TC - Trickle Charger for Break-A-Way
WIR - Wood Insert Ramps	7KA - 7K Dexter Axles w/16" 14-ply tires
FAR - Fully Adjustable Ramps	2 5/16"HDB - 2 5/16" Heavy Duty Ball Hitch
STM - Spare Tire Mount	CO - Color Options: Red, Blue or Green
3"EH - 3" Eye Hitch	