

HSE 14 Deluxe - 4 Ton



Standard Features

2" x 8" Treated Pine Deck	Diamond Plate Fenders
(2) 4500 lb. Dexter Axles	7:00 x 14.5 8-ply Tires
Adjustable 2 5/16" Ball Hitch	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	9,900 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	1,900 lbs.	Brakes	Electric / 12" x 2"
Maximum Payload	8,000 lbs. w/adequate hitch load	Wheels	14.5" x 6" Donut Type
Overall Length	20'	Tires	7:00 x 14.5 8-ply
Deck Length	14'	Jack Capacity	5,000 lb. w/Foot
Ramps	4' Cleated Fully Adjustable	Main Frame	6" Channel @ 8.2#
Overall Width	96"	Crossmembers	3" Channel @ 3.5#
Deck Width	78"	Decking	2" x 8" Treated Pine
Deck Height	23"	Tie Downs	4" Stake Pockets
Hitch	2 5/16" Ball Coupler	Lights	DOT approved
Hitch Height	22" to 26"	Colors	Yellow or Black
Axles	2-4500 lb. Dexter		

Options

6WGN - Gonsneck w/Adjustable 2 5/16" Ball Hitch	6W102 - 102" Wide w/82" Deck Width
TBB - Toolbox Bottom in Tongue	2BT - 2' Beavertail
LTBL - Lockable Toolbox Lid	CR - 10" Cargo Rail
6WOD - 2" x 8" Treated Oak Deck	JUSKTO7K - 7000 lb. Jack
4 1/2T - 4 1/2 Ton w/8:00 x 14.5 12-ply Tires	TC - Trickle Charger for Break-A-Way
5T - 5 Ton w/ST225 75/R 15" 8-ply Radial Tires	STM - Spare Tire Mount
2 1/2"EH - 2 1/2" Adjustable Eye Hitch	6WSATG - 6' Wide Spring Assisted Tailgate
6WARL - Additional Ramp Length (1" Maximum)	6WSSATG - 6' Wide Split Spring Assisted Tailgate
WIR - Wood Insert Ramps	NAH - Nonadjustable 2 5/16" Ball Hitch
NF - No Fenders	CO - Color Options: Red, Blue or Green
ASP - Additional Stake Pockets	