

## HTD20C - 12 Ton Tilt



### Standard Features

2" x 8" Treated Oak Deck	12,000 lb. Heavy Duty Landing Gear
(2) 12K Dexter Axles w/Oil Bath Bearings	16" 10-ply Radial Tires
Tool Tray in Tongue	Electric Brakes w/Break-A-Way

### Standard Specifications

<b>GVWR</b>	29,950 lbs.	<b>Brakes</b>	Electric/Self Adjusting 12 1/4" x 5"
<b>Empty Weight</b>	5,950 lbs.	<b>Wheels</b>	16" x 6" Dual 8-bolt
<b>Maximum Payload</b>	24,000 lbs. W/adequate hitch load	<b>Tires</b>	LT235/85R16" 10-ply
<b>Overall Length</b>	28'	<b>Jack Capacity</b>	12,000 lbs.
<b>Deck Length</b>	22' (13' flat, 9' tapered)	<b>Under Frame</b>	6" I-Beam @ 25#
<b>Overall Width</b>	96"	<b>Upper Deck</b>	8" I-Beam @ 18#
<b>Deck Width</b>	96"	<b>Crossmembers</b>	Double 3" Channel @ 7#
<b>Deck Height</b>	35"	<b>Side Rails</b>	6" Channel @ 8.2#
<b>Hitch</b>	3" Forged Eye	<b>Decking</b>	2" x 8" Treated Oak
<b>Hitch Height</b>	22" to 32"	<b>Tie Downs</b>	Rub Rail w/Stake Pockets
<b>Axles</b>	2-12K Dexter	<b>Lights</b>	DOT Sealed Rubber-Mounted
<b>Suspension</b>	Multi-Leaf Spring	<b>Colors</b>	Yellow or Black

### Options

12KAB - Air Brakes w/ABS & ASA	8WSD - Stationary Deck (4' Maximum)
5THW - 5th Wheel w/King Pin	8WADL - Additional Deck Length (4' Maximum)
8W5THW - 8' Wide 5th Wheel w/King Pin	8W102 - 102" Wide
LTBL - Lockable Toolbox Lid	STSLG - Single 2 Speed Landing Gear
MW - Modular Wiring	STM - Spare Tire Mount
TC - Trickle Charger for Break-A-Way	CO - Color Options: Red, Blue or Green