

HTD20D - 10 Ton Tilt



Standard Features

2" x 8" Treated Oak Deck	12,000 lb. Heavy Duty Landing Gear
(2) 10K Dexter Axles w/Oil Bath Bearings	16" 10-ply Radial Tires
Tool Tray in Tongue	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	25,950 lbs.	Brakes	Electric / Self Adjusting 12 1/4" x 4"
Empty Weight	5,950 lbs.	Wheels	16" x 6" Dual 8-bolt
Maximum Payload	20,000 lbs. Widesquare hitch load	Tires	LT235/85R16" 10-ply
Overall Length	28'	Jack Capacity	12,000 lbs.
Deck Length	22' (13' flat, 9' tapered)	Under Frame	6" J-Beam @ 25#
Overall Width	96"	Upper Deck	8" I-Beam @ 18#
Deck Width	96"	Crossmembers	Double 3" Channel @ 7#
Deck Height	35"	Side Rails	6" Channel @ 8.2#
Hitch	2 1/2" Forged Eye	Decking	2" x 8" Treated Oak
Hitch Height	22" to 32"	Tie Downs	Rub Rail w/Stake Pockets
Axles	2-10K Dexter	Lights	DOT Sealed Rubber-Mounted
Suspension	Multi-Leaf Spring	Colors	Yellow or Black

Options

10KAB - Air Brakes w/ABS & ASA	8WADL - Additional Deck Length (4' Maximum)
8WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	8W102 - 102" Wide
LTBL - Lockable Toolbox Lid	MW - Modular Wiring
8WSD - Stationary Deck (4' Maximum)	STM - Spare Tire Mount
TC - Trickle Charger for Break-A-Way	3" IH - 3" Eye Hitch
STSLG - Single 2 Speed Landing Gear	CO - Color Options: Red, Blue or Green